



# WHY RUN WITH APACHE?

AS720 SPRAYER

## THE APACHE MODEL AS720 SPRAYER

Comfort. Speed. Accuracy. Efficiency. That's exactly what you get from every Apache sprayer. They're built to handle the everyday (and not-so-everyday) field conditions with a higher standard of comfort and performance. And, because all we do is build sprayers, we're 100% focused on building the best sprayers in the industry, backed by the best warranty in the industry.

The Apache AS720 sprayer was engineered for the farmer looking for do-it-yourself control and peace of mind. Featuring a 750-gallon tank and mechanical drive, it's simple to operate and nimble enough to work in field conditions that the competitive sprayers can't. It's 10,600 pounds lighter than a Deere R4030, reducing yield-robbing compaction. When the days are long, its 28 mph road speed will get you to the next field (or home) faster.

Limited supply of AS720 sprayers with Tier 3 engines available at significant discount versus Tier 4 engine models. Ask your Apache dealer for details.

### UNIQUE FEATURES OF THE AS720

**Tank Capacity**

750 gallons

**Transmission**

JCB transmission  
Power Shift, 4-speed

**Engine**

Tier 3 160 hp  
Cummins engine

**Top Road Speed**

28 MPH

**Weight**

19,200 lbs (approx. dry weight)

**Crop Clearance**

42" with JCB planetary final drives  
50" clearance with 18" drop box all-gear final drives (optional)



# THE APACHE MODEL AS720 SPRAYER

## Specifications

|  |   |
|--|---|
| <b>Tank Capacity</b>                   | 750 gallons   |
| <b>Transmission</b>                    | JCB transmission Power Shift, 4-speed   |
| <b>Engine</b>                          | Tier 3 160 hp Cummins engine  |
| <b>Top Road Speed</b>                  | 28 MPH  |
| <b>Weight</b>                          | 19,200 lb (approximate dry weight)  |
| <b>Crop Clearance</b>                  | 42" with JCB planetary final drives<br>50" with 18" drop box all-gear final drives (optional) |
| <b>Fuel Capacity</b>                   | 100 gallons   |
| <b>Suspension</b>                      | Patented independent hydraulic  |
| <b>Brakes</b>                          | Fully-enclosed, self-adjusting, internal wet disc brakes                                      |
| <b>Front Tires</b>                     | 380/80R38 (narrow and semi-float options available)   |
| <b>Rear Tires</b>                      | 380/90R46 (narrow, semi-float and full-float options available)                               |
| <b>Transport Width and Height</b>      | 144" maximum  |
| <b>Overall Length</b>                  | 29" maximum   |
| <b>Booms</b>                           | ET custom boom straight 90' or 100' or 60'/90'<br>ET custom boom straight 120' or 132'        |
| <b>Product Pump</b>                    | HYPRO® hydraulically-driven centrifugal product pump  |
| <b>Rinse Tank</b>                      | 100 gallons   |
| <b>Cab</b>                             | ET custom pressurized state-of-the-art interior and console                                   |
| <b>Precision Application Equipment</b> | Raven Hawkeye™ or Trimble (factory installed)   |

All model year 2017 Apache sprayers are available with optional ISOBUS-ready wiring in lieu of factory installed field computers. Refer to your specific precision agriculture product documentation for compatibility information. Equipment Technologies factory installs all field computers using CAN bus wiring and protocols.

